



22
2622

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Docket No. 9601.00

Application of

Jim Henderson et al.

Serial No. 09/992,231

Filed: November 6, 2001

FOR: **MODULE**

**CLAIM FOR BENEFIT OF
EARLIER-FILED FOREIGN
APPLICATION**

JAN 10 2001

Group Art Unit: 2622

Examiner: **Unknown**

CERTIFICATE OF MAILING

I hereby certify that this correspondence is being deposited with the United States Postal Service as first class mail in an envelope addressed to: Assistant Commissioner for Patents, Washington, D.C. 20231 on JAN 10 2001 (Date of Deposit).


Shirley Doll

Assistant Commissioner for Patents

Washington, D.C. 20231

Sir:

RECEIVED

JAN 28 2002

Technology Center 2600

Applicants wish to claim the benefit of the filing date of the earlier G.B. Application Serial No. 0028475.2, filed on November 22, 2000, recited in the Declaration under the provision of 35 U.S.C. 119, and accordingly, Applicants submit herewith a certified copy of said application.

Respectfully submitted,



Michael Chan
Reg. No. 33,663
Attorney for Applicant(s)

NCR Corporation, Law Department, WHQ5E
1700 S. Patterson Blvd., Dayton, OH 45479-0001
Tel. No. 937-445-4956/Fax No. 937-445-3733

THIS PAGE BLANK (USPTO)



INVESTOR IN PEOPLE

The Patent Office
Concept House
Cardiff Road
Newport
South Wales
NP10 8QQ

RECEIVED
JAN 28 2002
Technology Center 2600

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Registration under the Companies Act does not constitute a new legal entity but merely affects the company to certain additional company law rules.


**CERTIFIED COPY OF
PRIORITY DOCUMENT**

Signed

Dated 3 September 2001

THIS PAGE BLANK (USPTO)

Patents Act 1977
(Rule 16)



23NOV00 E585819-7 D02073
P01/7700 0.00-0028475.2

Statement of inventorship and of right to grant of a patent

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)

1. Your reference

9601

RECEIVED

JAN 28 2002

Technology Center 2600

The Patent Office

Cardiff Road
Newport
South Wales NP9 1RH

22 NOV 2000

2. Patent application number
(The Patent Office will fill in this part)

0028475.2

3. Full name, address and postcode of the or of each applicant (underline all surnames)

NCR INTERNATIONAL, INC
1700 SOUTH PATTERSON BOULEVARD
DAYTON, OHIO 45479
UNITED STATES OF AMERICA

Patents ADP number (if you know it)

7409352001

If the applicant is a corporate body, give the country/state of its incorporation

INCORPORATED IN THE STATE OF DELAWARE

4.

MODULE

5. Name of your agent (if you have one)
"Address for service" in the United Kingdom to which all correspondence should be sent (including the postcode)

B WILLIAMSON
INTERNATIONAL IP DEPARTMENT
NCR LIMITED
206 MARYLEBONE ROAD
LONDON NW1 6LY

Patents ADP number (if you know it)

7791767001

6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and (if you know it) the or each application number

Country

Priority application number
(if you know it)

Date of Filing
(day/month/year)

7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application

Number of earlier application

Date of filing
(day/month/year)

8. Is a statement of inventorship and of right to grant of a patent required in support of this request? (Answer 'Yes' if:

- a) any applicant named in part 3 is not an inventor, or
 - b) there is an inventor who is not named as an applicant, or
 - c) any named applicant is a corporate body.
- See note (d))

YES

9. Enter the number of sheets for any of the following items you are filing with this form. Do not count copies of the same document.

Continuation sheets of this form

Description	20
Claim(s)	3
Abstract	1
Drawing(s)	5

10. If you are also filing any of the following, state how many against each item.

Priority documents

Translation of priority documents

Statement of inventorship and right to grant of a patent (Patents Form 7/77)

Request for preliminary examination (Patents Form 9/77)

1

Request for substantive examination (Patents Form 10/77)

Any other documents (please specify)

11.

I/We request the grant of a patent on the basis of this application.

Signature

Christine Sheppard

Date 22/11/2000

12. Name and daytime telephone number of person to contact in the United Kingdom

CHRISTINE SHEPPARD
020 7725 8379

Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

Notes

- If you need help to fill in this form or you have any questions, please contact the Patent Office on 01645 500505
- Write your answers in capital letters using black ink or you may type them.
- If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- If you have answered 'Yes' Patents Form 7/77 will need to be filed.
- Once you have filled in the form you must remember to sign and date it.
- For details of the fee and ways to pay please contact the Patent Office.

DUPLICATE

-1-

MODULE

The present invention relates to a module, particularly an item dispensing module such as a printer module, and to a terminal including such a module. In particular, the invention relates to a self-service terminal (SST), such as an automated teller machine (ATM), including such a module. The present invention also relates to a method of fulfilling pre-arranged transactions at a self-service terminal.

ATMs typically include a printer module for providing users with transaction receipts, mini statements, and such like. These printer modules typically include a print engine and a microcontroller for controlling the print engine.

The print engine performs printing functions, such as: feeding paper to a print head, printing data onto the fed paper, cutting the printed paper, and feeding the cut printed paper out through a receipt slot in an ATM's fascia for removal by a user.

The microcontroller provides the print engine with the commands and data necessary for performing these printing functions. The microcontroller also monitors the operation of the print engine and provides state of health information to an ATM controller. This state of health information includes the amount of paper remaining.

Printer modules are typically connected to the ATM controller by a secure serial channel because sensitive account information is sent to the printer module by the ATM controller.

There are a large number of ATMs installed throughout the world, most of them owned and operated by financial institutions, and many of these ATMs have printer modules. These ATMs are expensive to purchase and maintain. It is therefore desirable to use these ATMs for other functions in addition to providing financial transactions, so that additional revenue can be generated.

With the increase in electronic transactions, it has become common to purchase tickets by telephone using a credit or debit card.

One problem associated with this is that to enable a purchaser to redeem the ticket, a physical ticket has to be supplied because many venues are not able to accept electronic tickets. Posting a ticket to a purchaser introduces a delay, which makes postal delivery unsuitable for last minute purchase of tickets.

ATMs could be used to print tickets, but it is a complex task to route data through an ATM network. In addition, ATM networks are secure private networks, so many financial institutions would be unwilling to grant access to these networks to third party ticket suppliers.

According to a first aspect of the present invention there is provided a printer module comprising a print engine and a microcontroller, characterised in that the module includes a wireless receiver, whereby the module is operable to receive data from a remote source and to print the received data.

By virtue of this aspect of the invention, a printer module is provided having a wireless receiver so that a

third party can access the printer module directly, thereby bypassing any secure connection to the module, and instruct the module to print a ticket.

Preferably, the printer module includes an authentication component for validating that the remote source has permission to transmit data to the printer module. The authentication component may implement a cryptographic function, for example, to examine a digital certificate provided by the remote source.

Preferably, the wireless receiver is a wireless transceiver, such as a radio frequency (rf) transceiver, so that the transceiver is able to confirm printing to the remote source. If a transceiver is used, then the printer module is able to transmit state of health information, such as the amount of paper remaining in the printer module.

Preferably, the module further comprises a coupler for directing data received from the wireless receiver to the microcontroller. In some embodiments, the wireless receiver and/or the coupler may be incorporated in the microcontroller.

Preferably, a fixed channel is also connected to the coupler, so that the coupler is able to direct data received from the wireless receiver and/or from the fixed channel to the microcontroller. The fixed channel may be a serial or parallel data connection, using a wire or wireless transmission medium.

The microcontroller may store templates (each template representing a predefined image) received via the wireless

receiver, to avoid having to receive an image each time a ticket is to be printed.

The coupler may direct data received from both the fixed channel and the wireless receiver if customised data is to be printed together with, for example, financial data received from the fixed channel. For example, a header and footer containing advertising information may be printed on a mini statement; or a background image may be printed on a receipt. Having a wireless receiver for receiving the customised data allows the customised data to be changed very quickly, for example, between transactions. This allows financial institutions to sell advertising space on receipts to a third party without having to update a terminal's application program.

Preferably, the wireless receiver is powered by the printer module. This has the advantage that a separate power supply connection is not required.

According to second aspect of the invention there is provided a terminal comprising a controller in communication with a printer module, characterised in that the printer module includes a wireless receiver, whereby the module is operable to print data received from the controller and to print data received from a remote source via the wireless receiver.

The terminal may be a point of sale terminal, or a self-service terminal such as an ATM (automated teller machine) or a kiosk.

By virtue of this aspect of the invention, any logical and physical security implemented by the terminal is

unaffected by the wireless receiver, so that terminal security is not comprised.

When implemented on an ATM, no application changes to the ATM or to a remote transaction host are required. This ensures that a financial institution does not have to change the ATM software or operation.

Preferably, the module further comprises a coupler connected to a fixed channel from a terminal controller and connected to the wireless receiver, so that the coupler is able to direct data received from the fixed channel and/or the wireless receiver to the microcontroller.

The fixed channel may be a serial or a parallel data connection, using a wire or wireless transmission medium.

Preferably, the coupler provides printer access contention management to ensure that the terminal and a remote source do not access the printer module simultaneously.

The terminal may further comprise a display driven by the printer module so that the printer module may display information to a user.

One advantage of having an additional display is that the printer module can present a user with instructions independently of any controller within the terminal; thus, a new message can be displayed on the additional display without having to modify the application flow of the ATM controller program.

According to a third aspect of the invention there is provided a system for printing tickets at a terminal, the system comprising a terminal including a printer module

having a wireless receiver, and a server operable to establish a connection with the printer module via the wireless receiver and to transmit data for printing by the printer module.

The terminal may have a secure network connection to a transaction host for authorising transactions.

By virtue of this aspect of the invention the server is able to route instructions and data directly to the printer without having to route the instructions and data via the transaction host or the secure network.

According to a fourth aspect of the invention there is provided a method of printing tickets at a terminal, the method comprising the steps of: accessing a remote server using a wireless transceiver, providing the remote server with the identity of a terminal having a printer module including a wireless receiver, and requesting the remote server to print a ticket at the identified terminal by wireless transmission of data to the wireless receiver in the printer module.

According to a fifth aspect of the invention there is provided a method of retro-fitting a self-service terminal, the method comprising the steps of: identifying a self-service terminal having an item dispensing module; and modifying the item dispensing module by adding wireless receiver capability.

The item dispensing module may be a printer module, a cd writer module, a DVD writer module, a memory writer module, or such like.

The printer may be modified by adding a wireless receiver thereto to enable the module to receive and print data from a remote source.

By virtue of this aspect of the invention, an SST (such as an ATM) may be modified so that a user can purchase a ticket using a wireless device (such as a telephone or personal digital assistant), and print out the ticket using the SST's printer module. This enables a user to receive a printed ticket from any SST having a retro-fitted printer module.

As only the printer module has to be upgraded, the SST can be retro-fitted quickly and inexpensively to different types of SSTs and to SSTs from different manufacturers.

According to a sixth aspect of the invention, there is provided a method of fulfilling pre-arranged transactions at a self-service terminal, the method comprising the steps of: receiving by wireless communication from a remote location a request to fulfil a pre-arranged transaction; preparing a dispensable item for fulfilling the request; and dispensing the item to a user to fulfil the request.

The pre-arranged transaction may be a pre-paid transaction, such as a transaction where a valuable personalised item has been paid for, but has yet to be personalised and dispensed to fulfil the transaction.

The wireless communication may be received directly by a module having a wireless receiver. The module may be a printer module, a compact disc writer, a DVD writer, a card writer, a memory writer, or such like module that is capable of preparing an item for a user and for dispensing that item to the user. The module may customise the item for each

user, for example by including personal details relating to the user, or by allocating a licence (such as a copyright licence) to the user.

According to a seventh aspect of the present invention there is provided an item dispensing module comprising a dispensing engine and a microcontroller, characterised in that the module includes a wireless receiver, whereby the module is operable to receive instructions from a remote source via the wireless receiver and to dispense items according to the received instructions.

These and other aspects of the present invention will be apparent from the following specific description, given by way of example, with reference to the accompanying drawings, in which:

Fig 1 is a block diagram of a self-service terminal system according to one embodiment of the present invention;

Fig 2 is a schematic diagram of a self-service terminal of the system of Fig 1;

Fig 3 is a block diagram of a printer module of the terminal of Fig 2;

Fig 4 is a multi-layer diagram illustrating the components of one of the parts (the coupler) of the printer module of Fig 3;

Fig 5 is a flowchart illustrating the steps involved in a user obtaining a pre-purchased ticket using the system of Fig 1;

Fig 6 is a schematic diagram illustrating the data structure format of ticket information transmitted to the terminal of Fig 2;

Fig 7 is a multi-layer diagram illustrating a component (an alternative coupler) used in an alternative embodiment of the present invention; and

Fig 8 is a schematic diagram of a self-service terminal according to another embodiment of the present invention.

Referring now to Fig 1, which is a block diagram of a self-service terminal system 10. System 10 comprises a plurality of SSTs in the form of ATMs 12 (only two of which are shown) connected to a remote transaction host 14 by a secure private network 16. System 10 also comprises a Web server 18 including a modem 20.

The host 14 is owned and operated by a financial institution and includes an authorisation facility 22 and a back-office facility 24. As is well known in the art, the authorisation facility 22 authorises transactions received from the ATMs 12.

The back-office facility 24 includes details of bank accounts held by customers of the financial institution and stores information relating to transactions executed at the ATMs 12.

Reference is now made to Fig 2, which illustrates a user 30 operating an ATM 12, and shows the ATM 12 in more detail.

The ATM 12 includes a display module 32, a magnetic card reader/writer (MCRW) module 34, an encrypting keypad module 36, a printer module 38, an internal journal printer module 40, a deposit module 42, a cash dispenser module 44, an ATM controller module 46 for controlling the operation of the various modules, a network connection module 48 for

communicating with the remote transaction host 14 (Fig 1). All of the modules within the ATM 12 are interconnected by an internal bus 50 for securely conveying data.

As shown in Fig 2, modules 32 to 38, 42, and 44 are located behind a fascia 52, and align with apertures in the fascia 52. The user 30 in Fig 2 is holding a portable communication device 54 in the form of a WAP-enabled (wireless application protocol) cellular telephone such as a NOKIA 7110 (trade mark) cellphone.

Referring to Fig 3, which shows the printer module 38 in more detail, the printer module 38 comprises a print engine 60 controlled by a microcontroller 62 and fed with paper by a paper supply 64. The module 38 also comprises a wireless receiver 66 (in the form of a wireless modem) connected to the microcontroller 62 by a coupler 70. The coupler 70 is also connected to the ATM modules (32 to 36 and 40 to 48) by the internal bus 50 (a fixed channel).

The print engine 60, microcontroller 62, wireless receiver 66, and coupler 70 are all powered by the printer module 38, which receives power from a wiring harness (not shown) coupled to all the modules in the ATM 12.

A print data bus 74 connects the coupler 70 to the microcontroller 62; and a receiver bus 76 connects the wireless modem 66 to the coupler 70.

The print engine 60 includes a thermal print head 80 for applying print data to paper, and a knife 82 for cutting the printer paper.

The microcontroller 62 includes firmware for instructing the print engine to transport, print, and cut

the paper, so that a user is provided with a printed receipt or ticket.

Reference is now made to Fig 4, which is a multi-layer diagram illustrating the software and hardware components in the coupler 70.

The internal bus 50 and the print data bus 74 each couple to a respective physical socket 90, 92 in the form of an RS 232 connector. The receiver bus 76 couples to a physical socket in the form of a PCMCIA connector 94.

A printer service software component 96 contains drivers for the connectors 90, 92; and implements the low-level tasks of formatting data received or to be transmitted via the connectors 90, 92. The printer service 96 also implements the transmission protocol, and filters out data from a transmission.

Similarly, a wireless communication service software component 98 contains drivers for the connector 94; and implements the low-level tasks of formatting data received or to be transmitted via the connector 94. The wireless communication service 98 also implements the transmission protocol, and filters out data from a transmission.

The wireless communication service 98 includes a certificate authentication component 100 that implements any encryption scheme used and examines digital certificates received via the wireless modem 66 to determine their validity. The certificate authentication component 100 verifies that the data received via the wireless modem 66 is authentic to avoid a fraudulent third party printing data via the modem 66.

A management and inventory component 102 is in communication with both printer service 96 and wireless communication service 98. The management and inventory component 102 determines which bus (internal 50 or receiver 76) has access to microcontroller 62 at any given time; thereby avoiding any possible contention. The management and inventory component 102 also maintains the state of health of the print engine 60, particularly the amount of available paper; and records what templates, if any, are stored by microcontroller 62.

A wireless media application program 104 controls operation of the coupler 70 and determines factors such as what images are to be printed, at what time, and such like.

A typical transaction using printer module 38 to print a pre-purchased concert ticket will now be described with reference to Fig 5, which is a flowchart illustrating the steps involved in a user obtaining a pre-purchased ticket.

The user 30 purchases a ticket (step 200) in a conventional manner, for example using a credit or debit card, using a conventional sales channel, for example, a Web sales page or a telephone sales line. The user is then provided with an identifier by the sales channel.

When a ticket is allocated to this user (step 202) the identifier and the user's name is associated (step 204) with the allocated ticket. The identifier may be the telephone number of the user's cellular telephone 54, or some other convenient code.

The user then locates (step 206) and approaches an ATM 12 having a ticket printing facility. The ATM 12 may

include a poster or advertisement indicating that tickets may be printed using the ATM 12.

When the user 30 is at the ATM 12, the user 30 accesses (step 208) the server 18 using the cellphone 54. The URL associated with the server 18 may have been supplied to the user 30 when the ticket was purchased.

The server 18 supplies (step 210) a microbrowser in the user's cellphone 54 with a ticket fulfilment Web page displaying selectable options.

The user selects a 'local ticket printing' option using the cellphone's keypad. The server 18 receives this selection and provides the user 30 with a ticket identification Web page.

On the ticket identification Web page the user 30 enters using the cellphone's keypad his/her name and the ticket identifier (step 212) to indicate the ticket to be printed. The server 18 receives this selection and provides the user 30 with an ATM identifier Web page.

On the ATM identifier Web page the user 30 enters an ATM identification (step 214) to indicate what ATM the user is standing beside. The ATM identification is typically displayed on the ATM 12 in some convenient manner, for example, it may be printed on the ATM 12.

The user 30 is then provided with a Web page showing details of the ticket that is available for printing and having a field for requesting printing of this ticket.

After requesting printing of this ticket (step 216), the user waits for the ticket to be printed by the ATM 12.

Once the user 30 has requested printing of the ticket, the server 18 determines whether the request is valid (step 220). This involves checking that the identifier provided by the user 30 matches the identifier associated with the ticket sold to that user 30.

If the request is valid, then the server 18 obtains the telephone number (step 222) of the wireless modem 66 of the ATM 12 identified in step 214. The server 18 contains a lookup table (LUT) listing each ATM that has the ticket printing facility and the wireless modem telephone number associated with that ATM.

The server 18 then uses modem 66 to dial (step 224) the telephone number obtained from the LUT to establish a wireless connection with the printer module 38.

The server 18 then uses modem 20 to transmit ticket information and a digital authorisation certificate to the wireless modem 66 (Fig 3) to instruct printing of the ticket (step 226).

The printer module 38 then prints the ticket (step 228), and the user 30 removes (step 230) the ticket. The user 30 may then present the ticket at a concert venue in respect of which the ticket was sold for admission to the concert.

The server 18 awaits confirmation (step 232) from the printer module 38 that the ticket has been printed.

If, in step 220, the print request was not valid, then the transaction is aborted (step 234).

Referring again to Figs 3 and 4, and also to Fig 6, which shows the data structure format of ticket information

110, the printing step (step 228) will now be described in more detail.

In step 228, the wireless modem 66 receives the ticket information from the server's modem 18 and conveys this information to the coupler 70 via receiver bus 76.

The ticket information 110 has a sender field 112, a ticket data field 114, and a certificate field 116. The sender field 112 includes details of the server 18 transmitting the ticket information 110; the ticket data field 114 is a computer language description of the ticket to be printed; and the certificate field 116 includes a signed digital certificate guaranteeing that the ticket information was sent by the sender indicated in sender field 112.

The coupler 70 receives this ticket information 110 at the PCMCIA connector 94, and the wireless communication service 98 filters out the print data from the ticket data field 114 and the digital authorisation certificate from the certificate field 116.

The wireless communication service 98 conveys the print data to the management and inventory component 102, and conveys the digital authentication certificate to the certificate authentication component 100.

The certificate authentication component 100 examines the digital authentication certificate to ensure that the ticket information was transmitted by the server 18.

If the digital authentication certificate is not valid then the received print data is ignored and a response is

sent to the server 18 to indicate that the ticket will not be printed due to a certificate authentication failure.

If the digital authentication certificate is valid then the print data is conveyed through the management and inventory component 102 to the wireless media application 104.

The wireless media application 104 conveys the print data to the microcontroller 62 (via the management and inventory component 102, the printer service 96, and physical interface 92).

The microcontroller 62 receives this print data and controls the print engine 60 so that a ticket is printed conforming to the print data, and delivered to the user 30.

If the ticket is to be printed on special paper, then the microcontroller 62 ensures that the special paper is fed into the print engine when the ticket is to be printed.

If there is an error in printing (such as insufficient paper or a print head error) then the microcontroller 62 reports this error to the management and inventory component 102 (via the physical interface 92 and the printer service 96), which sends a message to the server 18 informing the server 18 that a ticket could not be printed.

If there is a fault with the printer 38 then the management and inventory component 102 may transmit a message to a service company to indicate that the printer module requires servicing.

If the server wishes to advertise tickets for sale, the server 18 may transmit advertising information referencing a template stored in the microcontroller 62. When the

wireless media application 104 receives this advertising information, it appends it to receipt data or mini statement data emanating from the ATM controller 46 on the internal bus 50, so that the microcontroller 62 prints a receipt or mini statement including the advertising information.

If the server wishes to use a new advertisement template, then the server 18 may transmit the new template to the microcontroller 62 via the wireless modem 66 and the coupler 70.

The management and inventory component 102 may store audit data relating to the number of tickets printed and the server 18 that requested printing of each ticket. This audit data may be used for charging each server 18 for the number of tickets printed.

Another embodiment of the present invention will now be described with reference to Fig 7, which is a multi-layer diagram illustrating an alternative coupler 270 and an associated display 306 in the form of an LCD panel 306.

Coupler 270 is similar to coupler 70 (Fig 4), but coupler 270 includes another physical interface 293 in the form of an LCD driver; and an advert service 297 that sends data to the LCD panel 306 via the LCD driver 293 and an LCD bus 308.

The server 18 can send information for displaying on the LCD panel 306 via the wireless modem 66 and the coupler 270. This enables the server 18 to provide a user with status information, such as "Your ticket is being printed", and with instructions, such as "Please remove your ticket from the receipt slot". This also enables the server 18 to

send advertisements to the LCD panel 306 to attract users of the ATM 12. As the advertisements, information, and instructions, are all sent directly from the server 18 to the printer module 38, the ATM application program does not require any modification.

Currently installed ATMs may be upgraded by retrofitting the ATM with the printer module described with reference to Fig 3. This involves removing a currently installed printer module from an ATM, and inserting the printer module described with reference to Fig 3. If an additional display 306 is used, then this may be mounted adjacent or in proximity to the currently installed ATM.

Yet another embodiment of the present invention will be described with reference to Fig 8, which is a schematic diagram of an alternative self-service terminal 412 in the form of an ATM being operated by a user 430. ATM 412 comprises a display module 432, a magnetic card reader/writer (MCRW) module 434, an encrypting keypad module 436, a printer module 438, an internal journal printer module 440, a cd writer module 441, a cash acceptor module 442, a cash dispenser module 444, an ATM controller module 446 for controlling the operation of the various modules, a network connection module 448 for communicating with the remote transaction host 14 (Fig 1). All of the modules within the ATM 412 are interconnected by an internal bus 450 for securely conveying data.

A typical transaction using ATM 412 is similar to the typical transaction described with reference to Fig 5, the main difference being that the user 430 may purchase a music

or software item using a cellular phone and receive the purchased item from the cd writer module 441 in the ATM 412.

Various modifications may be made to the above described embodiment within the scope of the invention, for example, parallel buses may be used instead of serial buses. Connectors other than RS232 and PCMCIA connectors may be used. In other embodiments, a user may access the server by dialling a telephone number associated with the server; the server's modem would automatically answers the call and presents the user with an audible and/or graphical menu of options to select using the user interface of the user's cellular telephone. Voice and text based menu options that may be selected using a telephone's keypad or using spoken commands are well-known. In other embodiments, the printer module controller may include a Web component for receiving print requests from the server 18 via the Web. In other embodiments, the microcontroller may determine whether a printed ticket has been removed by the user, and may send confirmation of removal of the ticket to the server. In other embodiments, a different protocol to WAP may be used by the user's cellphone. In other embodiments, the portable communication device may be a PDA having a wireless transceiver or a portable PC having a wireless transceiver. In other embodiments, the server may require a user to log in before they can request a ticket to be printed. The log in routine may require the user to enter a username and a passcode (comprising a sequence of characters such as letters and/or numbers); the user may then be able to review any tickets they have bought but not yet printed out. Although the specific embodiments relate primarily to tickets, it will be appreciated that the present invention

is also suitable to dispensing of other items, such as personalised financial instruments, coupons, passes, vouchers, other valuable media, and other customisable dispensable items.

Claims

1. A printer module (38) comprising a print engine (60) and a microcontroller (62), characterised in that the module (38) includes a wireless receiver (66), whereby the module (38) is operable to receive data from a remote source (18) and to print the received data.

2. A module according to claim 1, wherein the wireless receiver (66) is a wireless transceiver, so that the transceiver is able to confirm printing to the remote source (18).

3. A module according to claim 1 or 2, wherein the module (38) further comprises a coupler (70 or 270) for directing data received from the wireless receiver (66) to the microcontroller (62).

4. A module according to any of claims 1 to 3, wherein a fixed channel (50) is also connected to the coupler (70 or 270), so that the coupler (70 or 270) is able to direct data received from the wireless receiver (66) and/or from the fixed channel (50) to the microcontroller (62).

5. A module according to any preceding claim, wherein the microcontroller (62) stores templates, each template representing a predefined image, to avoid having to receive an image each time a ticket is to be printed.

6. A module according to any preceding claim, wherein the wireless receiver (66) is powered by the printer module.

7. A terminal (12) comprising a controller (46) in communication with a printer module (38), characterised in that the printer module (38) includes a wireless receiver (66), whereby the module (38) is operable to print data received from the controller (46) and to print data received from a remote source (18) via the wireless receiver (66).

8. A system (10) for printing tickets at a terminal (12), the system (10) comprising a terminal (12) including a printer module (38) having a wireless receiver (66), and a server (18) operable to establish a connection with the printer module (38) via the wireless receiver (66) and to transmit data for printing by the printer module (38).

9. A system according to claim 8, wherein the terminal is a point of sale terminal.

10. A system according to claim 8, wherein the terminal is a self-service terminal.

11. A method of printing tickets at a terminal, the method comprising the steps of: accessing a remote server using a wireless transceiver (step 208), providing the remote server with the identity of a terminal having a printer module including a wireless receiver (step 214), and requesting the remote server to print a ticket at the identified terminal by wireless transmission of data to the wireless receiver in the printer module (step 216).

12. A method of retro-fitting a self-service terminal, the method comprising the steps of: identifying a self-service terminal having an item dispensing module; and

modifying the item dispensing module by adding wireless receiver capability.

13. A method according to claim 12, wherein the item dispensing module is a printer module, and the printer is modified by adding a wireless receiver thereto to enable the module to receive and print data from a remote source.

14. A method of fulfilling pre-arranged transactions at a self-service terminal, the method comprising the steps of: receiving by wireless communication from a remote location a request to fulfil a pre-arranged transaction; preparing a dispensable item for fulfilling the request; and dispensing the item to a user to fulfil the request.

15. An item dispensing module comprising a dispensing engine and a microcontroller, characterised in that the module includes a wireless receiver, whereby the module is operable to receive instructions from a remote source via the wireless receiver and to dispense items according to the received instructions.

MODULE

Abstract

A module (38), a terminal (12) including the module, and a system (10) including the terminal (12), are described. The module may be a printer module (38) comprising a print engine (60), a microcontroller (62), and a wireless receiver (66), such as a wireless modem, so that the module (38) is operable to receive data from a remote server (18) and to print the received data. The module (38) also includes a coupler (70 or 270) for directing data received from the wireless modem (66) to the microcontroller (62) and for directing data from the terminal (12) to the microcontroller (62). A method of printing tickets at a terminal (12) and a method of retro-fitting a self-service terminal (12) are also described.

[Fig 3]




Fig 1




Fig 2

THIS PAGE BLANK (USPT




Fig 3





Fig 4

THIS PAGE BLANK (USPTO)

Fig 5

THIS PAGE BLANK (USPTO)




Fig 6




Fig 7

THIS PAGE BLANK (USPTO)




Fig 8

THIS PAGE BLANK (USPTO)